



Cv value of High Performance Butterfly Valve Class 600

SIZE		Degree of Opening								
inch	mm	10°	20°	30°	40°	50°	60°	70°	80°	90°
3	80	3	9	21	33	54	77	112	139	151
4	100	5	15	34	53	87	124	180	224	243
6	150	15	38	88	139	228	322	468	581	630
8	200	30	70	160	250	410	580	845	1050	1100
10	250	50	120	285	450	735	1040	1510	1875	2000
12	300	70	165	380	600	980	1390	2015	2505	2700
14	350	90	220	515	810	1330	1880	2730	3395	3700
16	400	125	305	705	1110	1820	2575	3735	4645	5100
18	450	135	325	765	1200	1965	2780	4035	5015	5500
20	500	195	470	1095	1715	2810	3980	5775	7180	7800
24	600	300	750	1750	2750	4500	6400	9250	11500	12500

<p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PRATT INDUSTRIAL. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PRATT INDUSTRIAL IS PROHIBITED.</p>	No.	Revision	Date	Drawn by	Title	File No.	
	0		10-6-14	AC		Cv value of High Performance Butterfly Valve Class 600	Date of Issue
				Checked by	DWG No.		Date of Issue
				Approved by		10-6-14	