



No.	Part Name
1	Body
2	Seat
3	Disc
4	Stem
5	Packing
6	Gland Flange
7	Bush Bearing
8	Disc Pin
9	Cap Packing
10	Cap
11	Seat Retainer
12	Seat Retainer

Test Pressure(FSHG)	API 598
Hydraulic	Air
Shaft	Seat
2225	1650

SIZE (inch)	A	B	G1	E1	L1	L2	C	T	Flanged Drilling				TOP WORKS						Gear		
									N1	H1	N2	Lug	M	P	R	S1	S	G2	X	ØW	
3	5.16	6.57	1.18	7.75	2.17	-	6.62	3/4"X10UNC	2	7/8	8	-	0.43	4	3.25	0.500	0.748	3.03	6.89	6.30	
4	5.95	7.68	1.26	8.94	2.52	7.48	8.50	7/8"X9UNC	2	1	8	4	0.55	4	5.00	0.624	0.874	3.74	8.98	11.02	

NOTE:  
 1. DESIGN : ANSI B16.34 & API 609  
 \*ON SIZES 3"-4" A FULL FACED GASKET IS RECOMMENDED  
 2. FLANGE CONNECTION : ANSI B16.5 CLASS 800  
 3. FACE TO FACE DIMENSION : API 609 CATEGORY B



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PRATT INDUSTRIAL. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PRATT INDUSTRIAL IS PROHIBITED.

No.	Revision	Date	Drawn by
			Kim,S.S
			Checked by Kim,S.S
			Approved by Choi,J.Y

Title	600WLF01
DWG No.	600WLF01
<b>HIGH PERFORMANCE VALVE 600# WAVER , LUGGED &amp; FLANGED TYPE</b>	

File No.	P600WLF03_04
Date of Issue	DO NOT SCALE
Date of Issue	2014-08-11
Rev.	